



Super Compact Turbo 2,2



Dimensions cm 40x54x161
 inch 15.7x21.3x63.3"



Central vacuum cleaner in steel painted in epoxy powder with single-phase turbine powered by induction (without brushes), side channel without transmission and with magnetic-thermal motor safety switch, built in 12 Volt inlets control and vacuum gauge, removable dust container, double-cyclone pre-filter chamber, industrial filter of special cloth with high withholding performance, manual filter shaking device, built-in utility valve, control panel, connections for linkage at piping network, CE certification, IP54 safety degree.

FOR TWO OPERATORS*


Super Compact Turbo 2,2 - SINGLE-PHASE		code 6409
Motor power	Kw	2,2@50Hz
Voltage requirement	V	220-240
Suction power max	mbar 320	inch H ₂ O 128"
Motor rotation	rpm	2880 - 3480
Airflow max	m ³ /h 306	CFM 180
Airflow @ 140 mbar	m ³ /h 244-285	CFM@56" 143-168
Airwatt @ Ø32mm	W	688
Volume filter chamber	l 70	gallons 18,5
Dust receptacle capacity	l 40	gallons 10,56
Filter surface	cm ² 7.100	sq. inch 1,100
Sound level	dB	68
Weight with packaging/net	kg 94/84,2	pound 207/185

* the second operator is granted only in domestic environment

NEW
 Professional electronic also for domestic purposes

For correct planning and installation have a look at our manuals.

Optional



Automatic self-cleaning filter device
 code IS91



Teflon® Filter, class "C"
 code ER244

Standard Polyester Filter,
 code ER255



Bag stretcher
 code 24-640



Disposable plastic bag
 code ER628